

# **6200 GAS 4 x 4 TRUCKS- 7/22**

**Entry Fee - \$5.00 gate admission & \$5.00 pit pass – Total \$10.00**

TRUCKS CAN BE TRAILED IN, BUT MUST MEET THE REST OF OUR RULES FOR THE STREET LEGAL CLASS, LICENSE AND REGISTRATION REQUIRED WITH CURRENT TAGS. **NO PASSENGERS. SEAT BELT MUST BE WORN. HELMET IS RECOMMENDED**

## **BODY**

TRUCKS COMPETING IN THIS CLASS MUST BE STOCK IN APPEARANCE. COMPLETE BED FLOORS, AND FACTORY GLASS, INNER FENDERS, INTERIORS ETC. NO GUTTING OF VEHICLE.

## **ENGINES & DRIVETRAIN**

- 1. THIS CLASS IS OPEN TO MODIFIED ENGINES.**
2. MUST BE SAME MAKE AS THE VEHICLE AND THERE IS NO CUBIC INCH LIMIT.
3. A SINGLE CARBURETOR OF ANY TYPE BASE ON A NATURAL ASPIRATED ENGINE.
4. NO TURBO OR SUPER CHARGED ENGINES ALLOWED. NO NITROUS OXIDE OR ALCOHOL ENGINES.
5. EXHAUST MUST EXIT THRU MUFFLERS AND PAST THE CAB OF THE TRUCK
6. AXLES, TRANSMISSION AND TRANSFER CASE MUST BE OEM FACTORY AND AVAILABLE IN A 1 TON OR LESS PICKUP.
7. SUSP. MUST HAVE 2" OF TRAVEL. TRACTION BARS ARE PERMITTED.
- 8. NO BLOCKED SUSPENSIONS**

## **WEIGHTS**

1. FRONT WEIGHTS AND BRACKETS MAY NOT EXTEND MORE THAN 195 INCHES FORWARD FROM THE CENTER OF REAR AXLE

## **FUEL**

1. RACING GAS PERMITTED IN THIS CLASS. NO ALCOHOL ENGINES.

## **HITCH**

1. MAY PULL OFF OF A REESE HITCH OR A PULLING TYPE HITCH MOUNTED SOLID TO THE FRAME WITH NO MOVEMENT.
2. MUST HAVE A 3.5 INCH HOLE FOR HOOK POINT. HOOK POINT MUST BE MINIMUM OF 36" FROM CENTER OF REAR AXLE, AND A MAXIMUM OF **24" HIGH**. NO PART OF THE HITCH MAY GO TO THE REAR AXLE.

## **TIRES**

1. ANY D.O.T. APPROVED TIRE IS PERMITTED. NO CUTTING OR SHARPENING OF TIRES PERMITTED.

**MANDATORY SAFETY:** ALL TRUCKS MUST HAVE 6" LONG U-JOINT SHIELDS COVERING REAR END YOKE, REAR OUT PUT YOKE, FRONT OUT PUT YOKE, AND FRONT END YOKE. THE FRONT OUT PUT YOKE COVER IS NOT REQUIRED IF LACK OF ROOM PREVENTS INSTALLATION. SHIELD THICKNESS REQUIREMENTS ALUMINUM MIN. 5/16" AND STEEL MIN. 1/4".

# **8000 Single Turbo Diesel 4 x 4 – 7/22**

**Entry Fee - \$5.00 gate admission & \$5.00 pit pass – Total \$10.00**

TRUCKS CAN BE TRAIERED IN, BUT MUST MEET THE REST OF OUR RULES FOR THE STREET LEGAL CLASS, LISCENSE AND REGISTRATION REQUIRED WITH CURRENT TAGS. **NO PASSENGERS. SEAT BELT MUST BE WORN. HELMET IS RECOMMEDED.**

## **BODY**

TRUCKS COMPETING IN THIS CLASS MUST BE STOCK IN APPEARANCE. COMPLETE BED FLOORS, AND FACTORY GLASS, INNER FENDERS, INTERIORS ETC. NO GUTTING OF VEHICLE.

## **ENGINES & DRIVETRAIN**

### **1. THIS CLASS IS OPEN TO MODIFIED STREET TRUCKS**

2. ENGINE, AND DRIVETRAIN MUST COME FACTORY IN A 1 TON OR LESS PICKUP.

3. **THIS CLASS IS OPEN TO TWINS and SINGLE CHARGER.** THE INDUCER BORE CAN'T EXCEED **2.80"**. THIS WILL BE TECHED USING A 2.85" PLUG, IF THE PLUG GOES IN YOU WILL BE DISQUALIFIED. NO REDUCERS OF ANY KIND PERMITTED TO MAKE A LARGER TURBO PASS INSPECTION. THIS ALSO INCLUDES WELDING AND REMACHINING INDUCER BORE TO MAKE A LARGER TURBO PASS. THE STOCK MAP WIDTH ENHANCEMENT (MWE) GROOVE IS ALLOWED. NO MWE GROOVE WIDER THAN A 1/4" WILL BE PERMITTED.

4. TRACTION BARS ARE PERMITTED AS LONG AS THEY DON'T RESTRICT SUSP. TRAVEL.

5. SMOKE MUST EXIT UP THROUGH STACKS IN THE BED OR YOU WILL NEED A TURN UP ON YOUR TAIL PIPE. NO EXCEPTIONS

## **WEIGHT**

1. FRONT WEIGHTS AND BRACKETS CAN'T EXCEED 60" FROM CENTER OF FRONT AXLE.

## **FUEL**

1. DIESEL FUEL AND BIO DIESEL ARE THE ONLY FUELS PERMITTED IN THIS CLASS.

2. WATER INJECTION **WILL BE PERMITTED.**

3. NO FUELS ADDED IN THE WATER ALLOWED

## **HITCH**

1. MUST PULL OFF OF A REESE TYPE HITCH, MOUNTED SOLID TO THE FRAME .

2. MUST HAVE 3.5 INCH HOLE FOR HOOK POINT. HOOKING POINT MUST BE THE FURTHEST POINT BACK OF THE TRUCK (min 48" from center of rear axle) AND A MAXIMUM OF 26" HIGH.

## **TIRES**

1. ANY D.O.T. APPROVED TIRE IS PERMITTED.

2. NO CUTTING OR SHARPENING OF TIRES PERMITTED.

**MANDATORY SAFETY:** ALL TRUCKS MUST HAVE 6" LONG U-JOINT SHIELDS COVERING REAR END YOKE, REAR OUT PUT YOKE, FRONT OUT PUT YOKE, AND FRONT END YOKE. THE FRONT OUT PUT YOKE COVER IS NOT REQUIRED IF LACK OF ROOM PREVENTS INSTALLATION. SHIELD THICKNESS REQUIREMENTS ALUMINUM MIN. 5/16" AND STEEL MIN. 1/4".